



Specifications:

	Outfits	DA1-180M	DA2-180M
Objective	Semi-plan Achromatic 4X, 10X, 40X, 100X	•	•
	Plan Achromatic 4X,10X, 20X, 40X, 60X,100X	0	0
	Infinite Plan Achromatic Objective System	0	0
Eyepiece	High Point & Wide Field EW10X/20	•	•
Viewing Head	Compensation Free Binocular Head at 30°,		
	Interpupilary Distance 55~75mm	•	
	Compensation Free Binocular Head at 30°,		•
	Interpupilary Distance 48~75mm		•
Nosepiece	Backward Quadruple	•	•
	Backward Quintuple	0	0
Stage	Double Layer Mechanical Stage 140×140mm, Moving Range 75×50mm	•	•
Audio-video System	1.3M Pixel CMOS Digital Camera with		
	High-resolution, 1280×1024, USB2.0 Output	•	•
	2.0M Pixel CMOS Digital Camera with	0	\sim
	High-resolution, 1600×1200, USB2.0 Output	0	0
	3.0M Pixel CMOS Digital Camera with	0	0
	High-resolution, 2048×1536, USB2.0 Output	U	U
Condenser	ABBE NA1.25 Condenser	•	●
Illumination	6V20W Halogen Lamp, Brightness Adjustable	•	•
	Kohler Illumination	0	0
Filter	Blue Filter	•	•
	Green Filter	•	●
Software	ScopeImage Advanced Micro-image Process	•	•
	ScopeImage Analysis Software	0	0
Optional	Phase Contrast Kit	0	0
	Polarization Attachment	0	0
	Dark-field Attachment	0	0
	LED Pointer	0	0